



GO KART OPERATIONS MINIMUM UNDERWRITING GUIDELINES

Named insured: _____

1. Participants must be required to wear shoes and seat belts.
2. No loose articles of clothing or long hair permitted unless properly secured.
3. Participants must meet the manufacturers recommended height requirement.
4. All karts with two seats must have them arranged side by side with safety belts for each seat.
5. All karts must be built and maintained to manufacturer's specifications.
6. All karts must:
 - a. be governed to a predetermined speed per ASTM standards
 - b. have passenger padding in place and in good condition (*seat bottom, seatback, steering wheel, headrest, steering column*)
 - c. have rollover protection
 - d. have chain and/or belt guards
 - e. have hot and/or moving parts properly guarded/shielded
 - f. have gas caps and all components in place and in proper working condition
 - g. have fuel tanks properly secured with no leaks
 - h. be free of fiberglass laceration hazards
7. Safety, warning, and instructional signage must be highly visible, in good repair, appropriately placed, and notes exposure risk.
8. A maintenance program should be in effect for the go-karts.
9. A minimum of two attendants should be on the track during operations.
10. No bumping or reckless driving shall be permitted.
11. The track must have a continuous containment system around the entire track with the exception of the pit entrance and exit.
12. Minimum of a 10lb B.C. rated fire extinguisher, properly mounted, marked, charged, and easily accessible to the pit attendants.
13. Minimum of a 10lb B.C. rated fire extinguisher, properly mounted, marked, charged, and easily accessible within 70 feet of any point on the track.
14. Entire perimeter restricts unauthorized access to track area.
15. Brake and gas controls return automatically, and properly labeled or color coded.

Applicant's Signature

Date (MM/DD/YYYY)

Applicant's Name (print)